

## Specifications

**BTUH:**.....SDV 30 - Hi 30,000  
Lo 21,000  
SDV 40 - Hi 40,000  
Lo 27,800

**Efficiency:** ..... Steady State - 85.80%  
Exceeds AFUE Requirements

**Flue Diameter:**.....Inner - 4"  
Outer - 6 5/8"

**Venting:**.....Coaxial - Wall or Roof

**Gas Supply:**..... Natural or LP

**Pilot System:** .....Piezo Spark

**Safety Controls:**..... ANSI/AGA Certified

**Safety Tested:**..... Warnock Hersey  
to AGA/ANSI  
Z21.11.1 & CAN 2.1  
Room Heater Std.

**Shipping Weight:**..... SDV 30 - 185 lbs.  
SDV 40 - 215 lbs.

## Standard Equipment:

Mendota stoves are painted metallic satin black with 24K gold plated grill rods. The SDV 40 comes with a 24K gold plated arch door (optional on SDV 30), fiber logset, log rack, 2-level burner, coal bed, neo-ceram one-piece glass bay window and blower with rheostat.

## Options:

- Thermostat
- Remote control/Thermostat
- Gold plated trivet plate
- 24K gold plated arched door (SDV 30)

Ask your dealer about custom painting the Mendota Stove to match any room decor.

**Warnock Hersey** Products, specifications, and prices subject to change without notice.



## Available in Two Sizes

	SDV 30	SDV 40
<b>A</b>	24 1/4"	29"
<b>B</b>	27 1/4"	29 1/4"
<b>C</b>	18 3/4"	18 3/4"
<b>D</b>	12 1/8"	14 1/2"
<b>E</b>	7 3/4"	7 3/4"
<b>F</b>	12"	24"
<b>G</b>	19 1/2"	30"
<b>H</b>	47"	59"
<b>I</b>	8"	10"
<b>J</b>	2"	2"
<b>K</b>	1 1/2"	1 1/2"

Consult owners manual for all final dimensions

